

Conditions

Ottoseal S9

Art.Nr.: s9 / manufacturer: [OTTO Chemie](#)



8,95EUR / cartridge

baseprice: 2,89EUR / 100 ml

incl. 19% VAT plus [shipping costs \(to DE\)](#)

Scaled Prices

from 20 Kartuschen	8,50EUR - you save 0,45EUR, baseprice: 2,74EUR / 100 ml
--------------------	--

 Delivery beginn within 1 - 3 days



Product Info:

Ottoseal S9 insulating edge seal to produce extremely UV-resistant Isolierglaseinheiten. Ottoseal S 9 is compatible with PVB film in laminated glass units.

- Neutral curing RTV-1 silicone sealant

Conditions

- Extremely UV resistant
- High tear and high impact strength
- Great adhesion to glass and many materials, some in conjunction with coupling agents
- Very well tolerated with spacers made of aluminum,
- Stainless steel and TPS
- Non-corrosive
- Compatible with PVB films for laminated safety glass units

Applications:

Secondary edge seal to produce UV-resistant insulating glass units in conjunction with butyl rubber as the primary seal.

Application Notes:

During application and curing of OTTOSEAL S9 is a good ventilated. OTTOSEAL S9 preparation and can be used immediately after appropriate opening of this container. Parts to be bonded must be clean, grease-free, dry and sustainable. As a cleaner, we recommend OTTO Cleaner T, methylated spirits or similar or automated cleaning equipment. The use of adhesion promoters ([Primer](#)) from OTTO program no intermediate standing are required. Because of the large number of possible influences during processing and the application is the user always make a sample processing and application. The concrete Aufbrauchsdatum is printed on the packaging printing and observed.

Processing:

Application temperature: +5 ° C to +35 ° C.

Mounting method ejaculate: With Hand Press pistol, air gun or gun battery.

Cleaning: with white spirit before curing, then with silicone or removed mechanically.

Smoothing and leveling agents with Abziehpachtel before skinning.

Storage:

Cool and dry at least 24 months shelf life.

Form:

310 ml cartridge (20 KTU. Per carton)

580 ml tube bag (20 bags per carton)

Conditions

Colors:

black

>> Technical Data

verfügbare Optionen

Lieferform

310 ml Kartusche
580 ml Schlauchbeutel (+3,26EUR)

Color

schwarz
