

## Conditions

### Ottoseal S54

Art.Nr.: s54 / manufacturer: [OTTO Chemie](#)



**9,29EUR**

baseprice: 3,00EUR / 100 ml

incl. 19% VAT plus [shipping costs \(to DE\)](#)

#### Scaled Prices

from 20	9,01EUR - you save 0,28EUR, baseprice: 2,91EUR / 100 ml
from 40	8,83EUR - you save 0,46EUR, baseprice: 2,85EUR / 100 ml
from 60	8,55EUR - you save 0,74EUR, baseprice: 2,76EUR / 100 ml
from 100	8,36EUR - you save 0,93EUR, baseprice: 2,70EUR / 100 ml

 Delivery beginn within 1 - 3 days

#### Product Info:

OTTOSEAL S54 Speziilsilikon B1 for sealing joints in difficult adhesive bases and a high temperature load such as asphalt, tar, glass, stainless steel, aluminum and some plastics. Ottoseal S54 is suited for bonding of EPDM, APTK and rubber.

## Conditions

- RTV-1 silicone sealant based on a modified amine system
- Flame-retardant according to DIN 4102-B1
- UV resistant
- Very good weathering and aging resistance

### Standards and tests:

- Tested and monitored according to DIN 4102-B1 - flame - by the Institute of Wood Science, University of Munich.
- For OTTOSEAL S54 is a general test certificate (ABP) in front with the number P-HFM 02 4 202nd

### Applications:

- Bonding of joints bands on polysulfide-based
- Bonding of EPDM and APTK profiles Joints with mastic asphalt screeds
- Sealing joints in difficult adhesive bases, such as Asphalt, tar, etc. For this we ask you to contact our application
- Voltage Balancing seal of similar and dissimilar materials such as Glass, stainless steel, aluminum and some plastics
- Due to the large number of different plastic materials, we recommend preliminary

### Processing:

Application temperature: +5 ° C to +35 ° C.

Mounting method ejaculate: With manual pressing, compressed air or battery gun.

Cleaning: with white spirit before curing, then with silicone or removed mechanically.

Smoothing and leveling agents with Abziehpachtel before skinning.

### Storage:

12 months from date of manufacture in unopened packaging in a cool (+5 ° C and +25 ° C) and dry storage. Protect from frost. Opened container tightly closed and short-term use.

### Form:

310 ml cartridge (20 KTU. Per carton)

## Conditions

Color:

gray, black, white

>> [Technical Data](#) >> [Safety data sheet](#) >> [Certificate \(DIN 4102\)](#)

### verfügbare Optionen

**Color**

grau  
schwarz  
weiß

---