

Conditions

Winfix Folienkleber

Art.Nr.: winfix / manufacturer: [Bosig](#)



7,44EUR

baseprice: 1,24EUR / 100 ml

incl. 19% VAT plus [shipping costs \(to DE\)](#)

 Delivery beginn within 24hrs

Product Info:

Sikaflex Construction Sealant is a polyurethane based on the engineering and building construction. Sikaflex Construction (D) is 1-part and is supplied ready to use. By reaction with moisture in air Sikaflex Construction (D) to a flexible sealant.

- Very short stringing
- Tack-free surface
- Movement capability 25%
- High tear resistance
- Bubble-free curing
- Very wide range of adhesion

Standards and tests:

Conditions

- ISO 11600 F 25 HM / 20 LM, SKZ Würzburg

Areas of application:

- Connection joints in buildings
- on windows and doors
- to shutter boxes, curtain walls, metal siding and concrete components

Movement joints in buildings

- on balconies
- on masonry
- to concrete
- in aerated

Processing:

Processing temperature: +5 ° C to +35 ° C.

Method: By Hand Press ejaculate gun, air gun or gun battery.

Cleaning: with white spirit before curing, and then with silicone or mechanically removed.

Smoothing: Smoothing with trowel and before skinning.

Storage:

Cool and dry at least 12 months from date of manufacture, egg cooler and dry storage in original, undamaged containers at temperatures between + 10 ° C and 25 ° C.

Note:

Sikaflex-Construction (D) should not be used for sealing glass in floor joints, in joints with constant exposure to water. Natural stone granite should be treated as a rule, such as concrete surfaces, other natural stones are attempts required please sit down in front of the application with your sales consultant.

The color can be affected by the action of environmental influences

be (chemicals, high temperature, UV radiation, especially when color "white"). The changes do not exclude the hue have no influence on the technical and protective properties of the product. Elastic sealants should never be painted.

Compatible with sealant coats the joint edges should be max. 1 mm cut (test according to DIN 52452-4). Not on bituminous substrates, or other oil or plasticizer hemorrhaging substrates such as EPDM or natural rubber insert (or preliminary tests or contact your sales representative). This product is not in the uncured state, isocyanate

Conditions

compounds, particularly alcohols, which are part of alcohol, for example, many paint thinners, cleaning agents and formwork oil, mixed or in contact be accommodated, since otherwise complete the reaction (crosslinking) of the material is disrupted or prevented. With Sikaflex-Construction (D) during the curing process a health risk, but potentially more intense odor develops after marzipan. Therefore interiors are revealed strengthened after installation and before use. For odor-sensitive interior spaces such as e.g. Schools and kindergartens, etc., we recommend the use of odorless material Sikaflex AT Connection.

Delivery form:

600 ml bag (20 KTU. Per box)

Color:

white, gray concrete,

verfügbare Optionen

Lieferform

600 ml Schlauchbeutel

Color

weiß
